



MEDO® PRO 30

wall- and ceiling-mounted light, round, 3000/4000 K, 10 W, DALI, Touch, 110°, white

Our design classic MEDO® has a new high-output addition: the MEDO® PRO. It impresses with its service life of L80B10@50,000h, eligible energy efficiency from 120 Im/W and a higher indirect light component. Efficiency is also the order of the day when it comes to installation, which is particularly fast thanks to our EasyBase. The improved protection code IP50 and an outstanding CRI >90 colour reproduction index ensure exceptional quality. Two elegant casing colours and a CCT switch that enables you to choose between 3000 K and 4000 K lets you personalise your lighting situation. The MEDO® PRO is available as a DALI and phase version, additionally you have the choice between opal (UGR <25) and prismatic (UGR <19) glass. As your most demanding projects deserve only the best lighting.



TECHNICAL DATA

Item no.	1007287
Number of different light outlets	2
IP Code	IP50
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	1
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0.9
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	1300/1300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	110 °



Light Source

A C	
Accessories	
MEDO 5 m suspension , black	
MEDO 5 m suspension , white	
SUSPENSION SET , for MEDO round pendant, round, black, 5-wire	
MEDO 5 m suspension , silver-grey	
SUSPENSION SET , for MEDO round pendant, round, white, 5-wire	
SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire	

Color	white/white
CRI	90
UGR≤	25
Service life	50000 h
Risk Group	1
Height	9.2 cm
Diameter	28 cm
Net weight	1.519 kg
Gross weight	2.166 kg
BIG WHITE Page	246