




MEDO® PRO 60

wall- and ceiling-mounted light, round, 3000/4000K, 39W, DALI, Touch, 80°, UGR<19, black

Our design classic MEDO® has a new high-output addition: the MEDO® PRO. It impresses with its service life of L80B10@50,000h, eligible energy efficiency from 120 lm/W and a higher indirect light component. Efficiency is also the order of the day when it comes to installation, which is particularly fast thanks to our EasyBase. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Two elegant casing colours and a CCT switch that enables you to choose between 3000 K and 4000 K lets you personalise your lighting situation. The MEDO® PRO is available as a DALI and phase version, additionally you have the choice between opal (UGR<25) and prismatic (UGR<19) glass. As your most demanding projects deserve only the best lighting.



Tekniske data

Item no.	1007300
Antal lysåbninger	2
IP klasse	IP50
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Surface
Monterings detaljer	Ceiling,Ceiling with Acc.,Wall
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjfnng	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	1000mA
IP Tæthedsgard	I
Watt	39 W
Omgivelsestemperatur	25 °C
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	5000/5100 lm
Farvetemperatur	3000/4000 Kelvin
Spredningsvinkel	80 °
Farve	matt black
CRI	90

Lyskilde

1807450	
Tilbehør	
1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

UGR ≤	19
LXXBXX-data	L80B10
Højde	9.2 cm
Diameter	60 cm
Nettovægt	5.101 kg
Bruttovægt	7.375 kg
BIG WHITE side	151