




MEDO® 30

wall- and ceiling-mounted light, round,
2700/3000/4000K, 12W, trailing-edge phase, 110°,
grey

The new MEDO® sets standards and impresses with a longer service life, better energy efficiency and a higher indirect light component. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Three elegant casing colours and a CCT switch that enables you to choose between 2700 K, 3000 K and 4000 K lets you personalise your lighting situation. And thanks to EasyBase, installation is as simple as it is fast.



Tekniske data

Item no.	1007318
Antal lysåbninger	2
IP klasse	IP50
IK Vandalklasse	IK02
Slagfaste	0.2 Joule
Montering	Surface
Monterings detaljer	Ceiling, Ceiling with Acc., Wall
Dæmpbar	Ja
Dæmpningstype	trailing edge
Antal lamper ved videresløjfning	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	250mA
IP Tæthedegrad	I
Watt	12 W
Omgivelsestemperatur	25 °C
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	30 °C
Lumen	1050/1100/1200 lm
Farvetemperatur	2700/3000/4000 Kelvin
Spredningsvinkel	110 °
Farve	matt gray
CRI	90

Lyskilde

1900642	
Tilbehør	
1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

UGR ≤	25
LXXBXX-data	L70B50
Højde	9.2 cm
Diameter	28 cm
Nettovægt	1.479 kg
Bruttovægt	2.125 kg
BIG WHITE side	161