




## NEW TRIA® 68

**recessed ceiling light, 2700 K, 38°, IP 20, round, white**

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700 K/3000 K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.



## TECHNICAL DATA

|                                 |                             |
|---------------------------------|-----------------------------|
| Item no.                        | 1007385                     |
| Rotating or tilting             | tiltable                    |
| IP Code                         | IP20                        |
| Dimmable                        | Yes                         |
| Dimming technology              | Leading edge, trailing edge |
| Primary nominal voltage         | 220-240V ~50/60 Hz          |
| Secondary power / voltage       | 200 mA                      |
| Safety class                    | II                          |
| Wattage                         | 8.3 W                       |
| Minimum ambient temperature     | -20 °C                      |
| Maximum ambient temperature     | 35 °C                       |
| Number of luminaires at LS B16A | 88                          |
| Number of luminaires at LS C16A | 149                         |
| Level of inrush current         | 3 A                         |
| Duration of inrush current      | 30 µs                       |
| Lumen                           | 705 lm                      |
| Colour temperature              | 2700 Kelvin                 |
| Beam angle                      | 38 °                        |
| Color                           | white                       |
| Risk Group                      | 1                           |
| Height                          | 4 cm                        |
| Diameter                        | 8.2 cm                      |

## Light Source

|        |                                                                                   |                              |          |
|--------|-----------------------------------------------------------------------------------|------------------------------|----------|
| 869193 |  | <b>Net weight</b>            | 0.204 kg |
|        |                                                                                   | <b>Gross weight</b>          | 0.246 kg |
|        |                                                                                   | <b>Shape of cut-out</b>      | round    |
|        |                                                                                   | <b>Installation depth</b>    | 4 cm     |
|        |                                                                                   | <b>Installation diameter</b> | 6.8 cm   |
|        |                                                                                   | <b>BIG WHITE Page</b>        | 105      |