



NEW TRIA®

LED module, round, 1800-3000K, 38°, PHASE, black

Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. A modular element is the LED MODULE, which is available with dim-to-warm technology (1800K-3000K) and different beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI>90 ensure exceptional quality. In addition, the NEW TRIA® LED MODULE impresses with its service life of L80-B10@50,000h.

Tekniske data

Item no.	1007421
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	Dim-to-Warm, Leading edge, trailing edge
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	250mA
Watt	11 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	35 °C
Lumen	70-700 lm
Farvetemperatur	1800-3000 Kelvin
Spredningsvinkel	38 °
Farve	matt black
CRI	90
LXXBXX-data	L80B10
Højde	3.9 cm
Diameter	5 cm
Nettovægt	0.16 kg
Bruttovægt	0.189 kg
BIG WHITE side	124

Lyskilde

	
--	---

Tilbehør

1007630	NEW TRIA® 75 XL , ceiling installation ring, D: 11 H: 2.6 cm, IP20, white
1007349	NEW TRIA® 75 , ceiling installation ring, L: 9 W: 9 H: 2.6 cm, IP 20, white
1007337	NEW TRIA® 68 , ceiling installation ring, D: 8.3 H: 3.55 cm, IP 65, incl. glass, white
1007634	NEW TRIA® 75 XL , ceiling installation ring, L: 11 W: 11 H: 2.6 cm, white
1007453	NEW TRIA® 68 , ceiling installation ring, recessed, D: 8.2 H: 4.4 cm, IP 20, white
1007346	NEW TRIA® 68 , ceiling installation ring, D: 8.2 H: 3.4 cm, IP 65, white
1007450	NEW TRIA® 75 , ceiling installation ring, recessed, attachment, D: 8.2 H: 4.9 cm, IP 20, white
1007328	NEW TRIA® 68 , ceiling installation ring, L: 8.2 W: 8.2 H: 2.6 cm, IP 20, white
1007489	NEW TRIA® 75 , ceiling installation ring, recessed, D: 8.2 H: 4.3 cm, IP 20, white
1007348	NEW TRIA® 68 , ceiling installation ring, L: 8.2 W: 8.2 H: 3.4 cm, IP 65, white
1007333	NEW TRIA® 68 , ceiling installation ring, D: 8.2 H: 2.6 cm, IP 20, white
1007339	NEW TRIA® 68 , ceiling installation ring, L: 8.3 W: 8.3 H: 3.55 cm, IP 65, incl. glass, white
1007342	NEW TRIA® 75 , ceiling installation ring, D: 9.3 H: 2.6 cm, IP 20, white