




## NEW TRIA® 68

**recessed ceiling light, 1800-3000 K, 60°, IP 20, round, white**

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are available as a complete set. The integrated LED MODULE, which is available with dim-to-warm technology (1800-3000 K) and different beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light, in black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.



## TECHNICAL DATA

|                                 |                             |
|---------------------------------|-----------------------------|
| Item no.                        | 1007425                     |
| Rotating or tilting             | tiltable                    |
| IP Code                         | IP20                        |
| Dimmable                        | Yes                         |
| Dimming technology              | Leading edge, trailing edge |
| Primary nominal voltage         | 220-240V ~50/60 Hz          |
| Secondary power / voltage       | 250 mA                      |
| Safety class                    | II                          |
| Wattage                         | 11 W                        |
| Minimum ambient temperature     | -20 °C                      |
| Maximum ambient temperature     | 35 °C                       |
| Number of luminaires at LS B16A | 85                          |
| Number of luminaires at LS C16A | 144                         |
| Level of inrush current         | 2 A                         |
| Duration of inrush current      | 30 µs                       |
| Lumen                           | 70-700 lm                   |
| Colour temperature              | 1800-3000 Kelvin            |
| Beam angle                      | 60 °                        |
| Color                           | white                       |
| Service life                    | 50000 h                     |
| Risk Group                      | 1                           |
| Height                          | 4 cm                        |

## Light Source

|        |                                                                                   |                       |          |
|--------|-----------------------------------------------------------------------------------|-----------------------|----------|
| 879017 |  | Diameter              | 8.2 cm   |
|        |                                                                                   | Net weight            | 0.219 kg |
|        |                                                                                   | Gross weight          | 0.264 kg |
|        |                                                                                   | Shape of cut-out      | round    |
|        |                                                                                   | Installation depth    | 4.5 cm   |
|        |                                                                                   | Installation diameter | 6.8 cm   |
|        |                                                                                   | BIG WHITE Page        | 109      |