




## NEW TRIA® UNIVERSAL 68

recessed ceiling light, 2500/3000/4000K, 60°, IP 20, square, black

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® UNIVERSAL 68 are available as a complete set. Lighting design options are provided by the integrated multi-wattage LED MODULE, which is variable in terms of output and light intensity and available with different beam angles (38°/60°). While the CCT switch allows easy selection between 2500K, 3000K and 4000K, the pivot range ensures flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



### Tekniske data

|                           |                             |
|---------------------------|-----------------------------|
| Item no.                  | 1007440                     |
| IP klasse                 | IP20                        |
| Montering                 | Recessed                    |
| Monterings detaljer       | Ceiling                     |
| Dæmpbar                   | Ja                          |
| Dæmpningstype             | Leading edge, trailing edge |
| Primær spænding           | 220-240V ~50/60Hz           |
| Sekundær strøm / spænding | 100-180mA                   |
| IP Tæthedegrad            | II                          |
| Watt                      | 8.6 W                       |
| Min omgivelsestemperatur  | -20 °C                      |
| Max omgivelsestemperatur  | 35 °C                       |
| Lumen                     | 540/600/600 lm              |
| Farvetemperatur           | 2500/3000/4000 Kelvin       |
| Spredningsvinkel          | 60 °                        |
| Farve                     | matt black                  |
| CRI                       | 90                          |
| LXXBXX-data               | L80B10                      |
| Længde                    | 8.2 cm                      |
| Bredde                    | 8.2 cm                      |
| Højde                     | 3.4 cm                      |
| Nettovægt                 | 0.215 kg                    |

Lyskilde

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 1807470 |  |
|---------|-----------------------------------------------------------------------------------|

|                        |         |
|------------------------|---------|
| Bruttovægt             | 0.26 kg |
| Indbygningsdybde       | 4 cm    |
| Installations diameter | 6.8 cm  |
| BIG WHITE side         | 137     |