




NEW TRIA® 75

ceiling installation ring, recessed, attachment, D: 8.2
H: 4.9 cm, IP 20, white

Discover the new generation of our NEW TRIA® series and configure an individual lighting experience. A modular element is the mounting ring, which is available as a pivoting and rotating or all-round protected IP 65 version. In the colours black, white, rose gold or brushed aluminium, it blends harmoniously into any room ambience. For easy assembly, the mounting ring, specially designed for a hole diameter of 75 mm, is supplied with clip and leaf springs.



TECHNICAL DATA

Item no.	1007450
IP Code	IP20
Color	white
Height	4.9 cm
Diameter	8.2 cm
Net weight	0.111 kg
Gross weight	0.135 kg
Shape of cut-out	round
Installation diameter	7.5 cm
BIG WHITE Page	122

Accessories

1007381	
1007431	NEW TRIA® UNIVER- SAL , LED module, 2500/3000/4000 K, 38°, PHASE, black
1007422	NEW TRIA®, LED mo- dule, round, 1800-3000 K, 60°, PHASE, black
1007384	
1007432	NEW TRIA® UNIVER- SAL , LED module, 2500/3000/4000 K, 60°, PHASE, black
1007383	
1007283	
1007382	
1007421	NEW TRIA®, LED mo- dule, round, 1800-3000 K, 38°, PHASE, black