




NEW TRIA® 75

ceiling installation ring, recessed, D: 8.2 H: 4.3 cm, IP 20, black

Discover the new generation of our NEW TRIA® series and configure an individual lighting experience. A modular element is the mounting ring, which is available as a pivoting and rotating or all-round protected IP 65 version. In the colours black, white, rose gold or brushed aluminium, it blends harmoniously into any room ambience. For easy assembly, the mounting ring, specially designed for a hole diameter of 75mm, is supplied with clip and leaf springs.



Tekniske data

Item no.	1007488
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Ceiling
Farve	matt black
Højde	4.3 cm
Diameter	8.2 cm
Nettovægt	0.08 kg
Bruttovægt	0.104 kg
Installations diameter	7.5 cm
BIG WHITE side	126

Tilbehør

1007381	NEW TRIA® , LED module, 2700K, 38°, PHASE, black
1007431	NEW TRIA® UNIVERSAL , LED module, 2500/3000/4000K, 38°, PHASE, black
1007422	NEW TRIA® , LED module, round, 1800-3000K, 60°, PHASE, black
1007384	NEW TRIA® , LED module, 3000K, 60°, PHASE, black
1007432	NEW TRIA® UNIVERSAL , LED module, 2500/3000/4000K, 60°, PHASE, black
1007383	NEW TRIA® , LED module, 3000K, 38°, PHASE, black
1007283	GU10 fitting for LED light (max. 10W) with quick installation box and strain relief
1007382	NEW TRIA® , LED module, 2700K, 60°, PHASE, black
1007421	NEW TRIA® , LED module, round, 1800-3000K, 38°, PHASE, black