





NOBLO® SPOT

1 ~ spot, round, 2700K, 6W, trailing-edge phase, 32°, grey

The rotating and pivoting NOBLO® SPOT shines across the board: quickly and easily mounted on the single-phase high-voltage track system, the new generation impresses with an improved colour reproduction index CRI>90, a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. Added to this is the high-quality light that creates a particularly cosy atmosphere in living areas, hotels and restaurants. Ideal for modern lighting concepts, made of high-quality aluminium, quickly installed and available in colour temperatures of 2700K and 3000K. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.



Tekniske data

Item no.	1007640
IP klasse	IP20
Montering	Surface
Monterings detaljer	Ceiling, Track Ceiling, Track Wall
Dæmpbar	Ja
Dæmpningstype	trailing edge
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	150mA
IP Tæthedsgard	I
Watt	6 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	740 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	32 °
Farve	matt gray
CRI	90
LXXBXX-data	L80B10
Længde	10.5 cm
Højde	10.7 cm
Diameter	5 cm
Nettovægt	0.256 kg

Lyskilde

	
Tilbehør	
1008484	NOBLO® , decorative ring, gold
1008487	NOBLO® , decorative ring, bronze
1008486	NOBLO® , decorative ring, copper
1008483	NOBLO® , decorative ring, white
1008482	NOBLO® , decorative ring, black
1008485	NOBLO® , decorative ring, grey

Bruttovægt	0.308 kg
BIG WHITE side	501