




UNIVERSAL TRACKSPOT V 3Ph.

25/30/35 W 927/930/940 24°-60° black

Discover our new technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the minimalist UNIVERSAL TRACKSPOT V three-phase spotlight, whose light colour (2700 K/3000 K/400 K) and light intensity can be adjusted via dip switches. Thanks to the multi-zoom function, the beam angle is also variable – from 24°, ideal for accent lighting, to 60° for homogeneous illumination. In addition, the high CRI >90 ensures the most lifelike color reproduction possible. Decide in favour of SLVtec today.



TECHNICAL DATA

Item no.	1007657
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK 05
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	620/750/850 mA
Safety class	I
Wattage	35 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10.22 A
Duration of inrush current	1660 µs
Lumen	3090/3470/3300 lm
Colour temperature	2700/3000/4000 Kelvin
Beam angle	24 °
Color	black/black
CRI	90
Service life	50000 h
Risk Group	1
Length	18.5 cm
Height	14.5 cm
Diameter	8 cm

Light Source

1807499		Net weight	0.796 kg
		Gross weight	1.024 kg
		BIG WHITE Page	1003