




LID I 75 free-standing lamp

29W, 2700/3000K, PHASE, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a high colour rendering index of over 80 and a long lifespan of 50,000 hours: the new LID I free-standing lamp emits a powerful light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



TECHNICAL DATA

Item no.	1007669
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly details	Ground
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	29 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	30
Number of luminaires at LS C16A	30
Level of inrush current	12 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	65 °C
Stroboscopic effect (SVM)	0.09
Lumen	1700/2000 lm
Colour temperature	2700/3000 Kelvin

Light Source

1807471	
---------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
--------	---------------------------------

Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	50000 h
Risk Group	0
Length	17 cm
Width	9.5 cm
Height	75 cm
Net weight	2.82 kg
Gross weight	3.017 kg
BIG WHITE Page	611