




## DASAR® S

recessed floor light, round, 4W, 3000K, 24°, IP67, cylindrical, anthracite

The DASAR® recessed floor lights are characterised by their high quality. The colour temperature of the symmetrical light diffusion can be adjusted via the CCT switch (2700K/3000K). While the mechanical load of the stainless steel-covered light is 2,000 kg, it is protected from all weather conditions thanks to its IP67 rating. The beam angle can be customised with three separately available and interchangeable reflectors (15°, 36°, 60°). The mounting housing, which is available separately, makes installation both quick and easy.



## TECHNICAL DATA

|                                       |                   |
|---------------------------------------|-------------------|
| Item no.                              | 1007680           |
| IP Code                               | IP67              |
| Impact resistance class               | IK 10             |
| Assembly                              | Recessed          |
| Assembly details                      | Ground with Acc.  |
| Mechanical loading                    | 2 t               |
| Primary nominal voltage               | 220-240V ~50/60Hz |
| Secondary power / voltage             | 200 mA            |
| Safety class                          | I                 |
| Wattage                               | 4 W               |
| Minimum ambient temperature           | -20 °C            |
| Maximum ambient temperature           | 45 °C             |
| Number of luminaires at LS B16A       | 112               |
| Number of luminaires at LS C16A       | 224               |
| Level of inrush current               | 10 A              |
| Duration of inrush current            | 100 µs            |
| Temperature at glass (light emission) | 60 °C             |
| Stroboscopic effect (SVM)             | 0.01              |
| Lumen                                 | 350 lm            |
| Colour temperature                    | 3000 Kelvin       |
| Beam angle                            | 24 °              |
| Color                                 | stainless steel   |

## Light Source

|         |   |
|---------|---|
| 1642674 |  |
|---------|---|

## Accessories

|         |                                |
|---------|--------------------------------|
| 1007682 | Mounting housing for DASAR® S  |
| 1007684 | Reflector for DASAR® S/M , 36° |
| 1007683 | Reflector for DASAR® S/M , 15° |
| 1007685 | Reflector for DASAR® S/M , 50° |

|                       |          |
|-----------------------|----------|
| CRI                   | 80       |
| LXXBXX data           | L80B50   |
| Service life          | 50000 h  |
| Depth                 | 11.5 cm  |
| Diameter              | 10.5 cm  |
| Net weight            | 0.6 kg   |
| Gross weight          | 0.642 kg |
| Shape of cut-out      | round    |
| Installation depth    | 15 cm    |
| Installation diameter | 18 cm    |
| BIG WHITE Page        | 833      |