




DASAR® S

recessed floor light, square, 4W, 3000K, 24°, IP67, cylindrical, anthracite

The DASAR® recessed floor lights are characterised by their high quality. The colour temperature of the symmetrical light diffusion can be adjusted via the CCT switch (2700K/3000K). While the mechanical load of the stainless steel-covered light is 2,000 kg, it is protected from all weather conditions thanks to its IP67 rating. The beam angle can be customised with three separately available and interchangeable reflectors (15°, 36°, 60°). The mounting housing, which is available separately, makes installation both quick and easy.



Tekniske data

Item no.	1007681
IP klasse	IP67
IK Vandalklasse	IK10
Montering	Recessed
Monterings detaljer	Ground with Acc.
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	200mA
IP Tæthedsggrad	I
Watt	4 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	350 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	24 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B50
Længde	9.5 cm
Bredde	9.5 cm
Dybde	11.5 cm
Nettovægt	0.661 kg

Lyskilde

	
Tilbehør	
1007682	Mounting housing for DASAR® S
1007684	Reflector for DASAR® S/M , 36°
1007683	Reflector for DASAR® S/M , 15°
1007685	Reflector for DASAR® S/M , 50°

Bruttovægt	0.817 kg
Indbygningsdybde	15 cm
Installations diameter	18 cm
BIG WHITE side	833