




MODELA

wall light, up/down, 2700K, PHASE, black/gold

With golden housing accents, the unusually shaped MO-DELA up/down wall lights take the colour trend outside. The IP65-certified outdoor lights are also available in a single colour in white or black. In any case, the light cones beams radiating upwards and downwards make it possible to set warm white (2700 K) and dimmable accents. Ideal for illuminating facades in an elegant, atmospheric and long-lasting way (L80, 50,000h).



TECHNICAL DATA

Item no.	1007807
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	65
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	95 mA
Safety class	I
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	213
Number of luminaires at LS C16A	213
Level of inrush current	3.44 A
Duration of inrush current	48.4 µs
Temperature at glass (light emission)	58 °C
Stroboscopic effect (SVM)	0.01

Light Source

1907083	
---------	---

Lumen	810 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	black
CRI	80
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Width	9.7 cm
Height	20.2 cm
Depth	9 cm
Net weight	0.62 kg
Gross weight	0.663 kg