




MODELA

wall light, up/down, 2700K, PHASE, black

With golden housing accents, the unusually shaped MO-DELA up/down wall lights take the colour trend outside. The IP65-certified outdoor lights are also available in a single colour in white or black. In any case, the light cones beams radiating upwards and downwards make it possible to set warm white (2700 K) and dimmable accents. Ideal for illuminating facades in an elegant, atmospheric and long-lasting way (L80, 50,000h).



TECHNICAL DATA

| | |
|---------------------------------------|----------------|
| Item no. | 1007808 |
| Number of different light outlets | 2 |
| IP Code | IP65 |
| Impact resistance class | IK 07 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Number of through-wires | 65 |
| Primary nominal voltage | 220-240V ~50Hz |
| Secondary power / voltage | 95 mA |
| Safety class | I |
| Wattage | 7.5 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 213 |
| Number of luminaires at LS C16A | 213 |
| Level of inrush current | 3.44 A |
| Duration of inrush current | 48.4 µs |
| Temperature at glass (light emission) | 58 °C |
| Stroboscopic effect (SVM) | 0.01 |

Light Source

| | |
|---------|---|
| 1907083 |  |
|---------|---|

| | |
|---------------------------|-------------|
| Lumen | 770 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Width | 9.7 cm |
| Height | 20.2 cm |
| Depth | 9 cm |
| Net weight | 0.62 kg |
| Gross weight | 0.663 kg |