




DASAR® M

recessed floor light, round cover, 24°, 3000K, incl. DALI driver, stainless steel

Experience the highest quality of light with unique ease of installation. In addition, the DALI-controllable DASAR® recessed floor lights with a lifespan of 50,000 hours (L80-B50) set standards in terms of efficiency. The interchangeable reflectors with different beam angles of 15°, 30° and 50° offer a great deal of design freedom to effectively set the scene for facades. The reflectors can also be pivoted by 30°. And thanks to the separately available recessed fixing kit, the installation can be optimally adapted to your project planning.



Tekniske data

Item no.	1007810
IP klasse	IP67
IK Vandalklasse	IK10
Montering	Recessed
Monterings detaljer	Ground with Acc.
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjfnig	20
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	300mA
IP Tæthedsgrad	I
Watt	6.5 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	450 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	24 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B50
Dybde	14 cm

Lyskilde

	
Tilbehør	
1007684	Reflector for DASAR® S/M , 36°
1007683	Reflector for DASAR® S/M , 15°
1007685	Reflector for DASAR® S/M , 50°
1007822	Mounting housing , for DASAR® M

Diameter	13 cm
Nettovægt	1.152 kg
Bruttovægt	1.382 kg
Indbygningsdybde	18 cm
Installations diameter	31 cm