




## DASAR® M

recessed floor light, square cover, 24°, 3000K, incl.  
DALI driver, stainless steel

Experience the highest quality of light with unique ease of installation. In addition, the DALI-controllable DASAR® recessed floor lights with a lifespan of 50,000 hours (L80-B50) set standards in terms of efficiency. The interchangeable reflectors with different beam angles of 15°, 30° and 50° offer a great deal of design freedom to effectively set the scene for facades. The reflectors can also be pivoted by 30°. And thanks to the separately available recessed fixing kit, the installation can be optimally adapted to your project planning.



### Tekniske data

|                                  |                      |
|----------------------------------|----------------------|
| Item no.                         | 1007811              |
| IP klasse                        | IP67                 |
| IK Vandalklasse                  | IK10                 |
| Montering                        | Recessed             |
| Monterings detaljer              | Ground with Acc.     |
| Dæmpbar                          | Ja                   |
| Dæmpningstype                    | DALI,Touch           |
| Antal lamper ved videresløjfning | 20                   |
| Mekanisk belastning              | 2 t                  |
| Primær spænding                  | 220-240V ~50/60Hz    |
| Sekundær strøm / spænding        | 300mA                |
| IP Tæthedsgrad                   | I                    |
| Watt                             | 6.5 W                |
| Min omgivelsestemperatur         | -20 °C               |
| Max omgivelsestemperatur         | 40 °C                |
| Lumen                            | 450 lm               |
| Farvetemperatur                  | 3000 Kelvin          |
| Spredningsvinkel                 | 24 °                 |
| Farve                            | matt stainless steel |
| CRI                              | 80                   |
| LXXBXX-data                      | L80B50               |
| Længde                           | 12 cm                |

Lyskilde

|                 |                                                                                   |
|-----------------|-----------------------------------------------------------------------------------|
|                 |  |
| <b>Tilbehør</b> |                                                                                   |
| 1007684         | Reflector for DASAR® S/M , 36°                                                    |
| 1007683         | Reflector for DASAR® S/M , 15°                                                    |
| 1007685         | Reflector for DASAR® S/M , 50°                                                    |
| 1007822         | Mounting housing , for DASAR® M                                                   |

|                        |          |
|------------------------|----------|
| Bredde                 | 12 cm    |
| Dybde                  | 14 cm    |
| Nettovægt              | 1.179 kg |
| Bruttovægt             | 1.404 kg |
| Indbygningsdybde       | 18 cm    |
| Installations diameter | 31 cm    |