




## Q-RING

wall light, sensor, 3000K, IP54, black

The new Q-RING family elegantly picks up on the trend towards organic shapes. The indirect and warm white light (3000 K) illuminates façades discreetly and glare-free. Thanks to the special surface treatment, it can also be used in coastal areas. The integrated sensor system ensures optimum lighting and safety around the clock.



### Tekniske data

|                                 |                   |
|---------------------------------|-------------------|
| Item no.                        | 1007916           |
| IP klasse                       | IP54              |
| IK Vandalklasse                 | IK06              |
| Slagfasthed                     | 2 Joule           |
| Montering                       | Surface           |
| Monterings detaljer             | Wall              |
| Antal lamper ved videresløjning | 20                |
| Primær spænding                 | 220-240V ~50/60Hz |
| Sekundær strøm / spænding       | 240mA             |
| IP Tæthedsgard                  | I                 |
| Watt                            | 10 W              |
| Min omgivelsestemperatur        | -20 °C            |
| Max omgivelsestemperatur        | 40 °C             |
| Lumen                           | 950 lm            |
| Farvetemperatur                 | 3000 Kelvin       |
| Farve                           | black             |
| CRI                             | 80                |
| LXXBXX-data                     | L80B50            |
| Dybde                           | 11 cm             |
| Diameter                        | 27 cm             |
| Nettovægt                       | 1.068 kg          |
| Bruttovægt                      | 1.771 kg          |

Lyskilde

|         |                                           |
|---------|-------------------------------------------|
| 2011210 | <div><div>A<br/>G</div><div>C</div></div> |
|---------|-------------------------------------------|