



FLAC BEAM

outdoor façade light, LED, 3000K, IP65, stone-grey, with Philips DLMi module 1600Im, 27W, incl. UK Plug

The FLAC BEAM outdoor floodlights are fitted with high-performance LED modules made by Philips. The floodlight is made of aluminium and, thanks to the fitted mounting bracket, is suitable for installation on the wall, ceiling and floor. The electrical connection of the swivelling and tilting floodlight is made using the built-in two metre connection lead which includes an IP protected contact plug directly to the 230V mains supply. The floodlight has IP65 protection class and with 1600 lm, it is suitable for outdoor use. In addition, a HIT version for discharge lamps is available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1007942
Rotating or tilting	rotary bar and tiltable
IP Code	IP65
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	1
Wattage	27 W
Ambient temperature	35 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Stroboscopic effect (SVM)	0.05
Lumen	1600 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Height	22 cm
Diameter	17 cm



Net weight	2.58 kg
Gross weight	2.761 kg