



SUN 20

ceiling-mounted light, round, 1x max. 60W, E27, black

The timeless design and elegant style of the SUN family of luminaires is sure to put a smile on every face. The sunny members now consist of wall and ceiling-mounted lights, pendant lights and table lamps, all of which are fitted with high-quality opal glass shades. The different shapes, colours and sizes offer a wide range of design options. Equip an entire room with the SUN family and create a lighting experience that is as functional as it is aesthetically pleasing.



TECHNICAL DATA

Item no.1008125SocketE27Number of sockets1IP CodeIP20Impact resistance classIK 02AssemblySurfacePrimary nominal voltage220-240V ~50/60 HzSafety classIWattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kgGross weight1.36 kg		
Number of sockets1IP CodeIP20Impact resistance classIK 02AssemblySurfacePrimary nominal voltage220-240V ~50/60 HzSafety class1Wattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Item no.	1008125
IPIPIP20Impact resistance classIK 02AssemblySurfacePrimary nominal voltage220-240V ~50/60 HzSafety class1Wattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Socket	E27
Impact resistance classIK 02AssemblySurfacePrimary nominal voltage220-240V ~50/60 HzSafety class1Wattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Number of sockets	1
AssemblySurfacePrimary nominal voltage220-240V ~50/60 HzSafety classIWattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	IP Code	IP20
Primary nominal voltage220-240V ~50/60 HzSafety classIWattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Impact resistance class	IK 02
Safety classIWattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Assembly	Surface
Wattage60 WMinimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Primary nominal voltage	220-240V ~50/60 Hz
Minimum ambient temperature-20 °CMaximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Safety class	1
Maximum ambient temperature40 °CColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Wattage	60 W
ColorblackHeight22 cmDiameter20 cmNet weight0.8 kg	Minimum ambient temperature	-20 °C
Height 22 cm Diameter 20 cm Net weight 0.8 kg	Maximum ambient temperature	40 °C
Diameter 20 cm Net weight 0.8 kg	Color	black
Net weight 0.8 kg	Height	22 cm
	Diameter	20 cm
Gross weight 1.36 kg	Net weight	0.8 kg
	Gross weight	1.36 kg



Recommended lamp

1005289

T38 E27 , white LED light, 8W 3000K CRI90 240°