



RASTERLYSWL

wall-mounted light, rectangular, 2700/3000K, 14W, PHASE, 70°, anthracite

The architecturally extremely appealing RASTERLYS utilises sophisticated lighting technology that enables uniform illumination with a high level of visual comfort. The attractive shape leaves a lasting impression in gardens, house entrances or on facades, balconies, terraces and outdoor areas of shops, restaurants and other business premises. Thanks to its IP65 protection class and high-quality coating, it can withstand any weather. To create the perfect lighting mood, you can set the colour temperature (2700-K/3000K) via CCT switch.

Tekniske data

Item no.	1008384
Antal lysåbninger	1
IP klasse	IP65
IK Vandalklasse	IK06
Slagfasthed	1 Joule
Montering	Surface
Dæmpbar	Ja
Dæmpningstype	Leading edge, trailing edge
Antal lamper ved videresløjfnig	50
Primær spænding	220-240V ~50/60 Hz
Sekundær strøm / spænding	350 mA
IP Tæthedsgrad	I
Watt	14 W
Omgivelsestemperatur	0 °C
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	350/400 lm
Farvetemperatur	2700/3000 Kelvin
Farve	anthracite
CRI	80
Bredde	12 cm
Højde	21 cm

Dybde	7.6 cm
Nettovægt	0 kg
Bruttovægt	0 kg