




KADUX

recessed ceiling light, double, 3000 K, DALI 2, touch, 30°, black

Experience high light output and efficiency for use in shops and retail environments: KADUX is our gimbal-mounted recessed ceiling luminaire, available as a single or double-lamp version in white or black and various colour temperatures (3000 K/4000 K). Thanks to the quick-connection box in a closed steel housing, the light is easy to install and is both robust and durable.



TECHNICAL DATA

Item no.	1008572
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	30
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	1400 mA
Safety class	II
Wattage	54 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	36
Level of inrush current	9.1 A
Duration of inrush current	174 µs
Lumen	6300 lm
Colour temperature	3000 Kelvin

Light Source

1411562	
Beam angle	30 °
Color	black/black
CRI	90
Binning	6 SDCM
Service life	50000 h
Risk Group	1
Length	37 cm
Width	19.5 cm
Height	12.5 cm
Net weight	2.8 kg
Gross weight	3.24 kg
Shape of cut-out	square
Installation length	34.5 cm
Installation width	17 cm
Installation depth	12.5 cm
BIG WHITE Page	19