




PANEL C

625 34 W 830/840 UGR

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the PANEL C luminaires, which impress with their high energy efficiency of over 130 lm/W and a long service life of L80B10-70,000 hours. They are available in three sizes, with all versions also available as DALI versions. Thanks to the glare-free light with a UGR<19, they are ideal for basic lighting in offices.



Tekniske data

Item no.	1008598
IP klasse	IP20/IP54
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Primær spænding	220-240V ~50/60 Hz
Sekundær strøm / spænding	850
IP Tæthedsgrad	II
Watt	34 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	4550/4650 lm
Farvetemperatur	3000/4000 Kelvin
Farve	white
CRI	80
UGR ≤	19
Længde	62 cm
Bredde	62 cm
Højde	2.8 cm
Nettovægt	1.92 kg
Bruttovægt	2.44 kg
Indbygnings længde	59 cm

Indbygningsbredde	59 cm
Indbygningsdybde	8 cm

Tilbehør

1008610	PANEL C , 4x mounting springs
1008609	PANEL C , suspension cable, L: 150 cm