




OCULUS

surface-mounted ceiling light, round, 2000-3000K, 11-W, dim-to-warm, PHASE, 100°, dark copper

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light, every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting. In addition to the classic black and white versions, all OCULUS lights are also available in three other elegant colours. The high-quality PVD coating ensures outstanding surface properties.



Tekniske data

Item no.	1008620
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Surface
Dæmpbar	Ja
Dæmpningstype	trailing edge
Primær spænding	220-240V ~50/60 Hz
Sekundær strøm / spænding	250 mA
IP Tæthedsgard	I
Watt	11 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	50 °C
Lumen	36-780 lm
Farvetemperatur	2000-3000 Kelvin
Farve	dark copper
CRI	90
Højde	9 cm
Diameter	9 cm
Nettovægt	0.57 kg
Bruttovægt	0.72 kg