




# DOWNLIGHT C

## DALI 150 20W 930 IP54

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.



## Tekniske data

|                                  |                    |
|----------------------------------|--------------------|
| Item no.                         | 1008625            |
| IP klasse                        | IP54               |
| IK Vandalklasse                  | IK02               |
| Slagfasthed                      | 0.2 Joule          |
| Montering                        | Recessed           |
| Dæmpbar                          | Ja                 |
| Dæmpningstype                    | DALI               |
| Antal lamper ved videresløjfning | 18                 |
| Primær spænding                  | 220-240V ~50/60 Hz |
| Sekundær strøm / spænding        | 500 mA             |
| IP Tæthedsggrad                  | II                 |
| Watt                             | 20 W               |
| Min omgivelsestemperatur         | -20 °C             |
| Max omgivelsestemperatur         | 40 °C              |
| Lumen                            | 2250 lm            |
| Farvetemperatur                  | 3000 Kelvin        |
| Farve                            | white              |
| CRI                              | 90                 |
| UGR ≤                            | 22                 |
| Højde                            | 8.6 cm             |
| Diameter                         | 17.6 cm            |
| Nettovægt                        | 0.5 kg             |

|                               |         |
|-------------------------------|---------|
| <b>Bruttovægt</b>             | 0.6 kg  |
| <b>Indbygningsdybde</b>       | 9 cm    |
| <b>Installations diameter</b> | 15.5 cm |