




MEDO® 40

recessed ceiling light, frame, 3000/4000K, 80°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frameless. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



Tekniske data

Item no.	1008631
IP klasse	IP20
Montering	Recessed
Sekundær strøm / spænding	500 mA
IP Tæthedsgad	III
Watt	16 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	2350/2450 lm
Farvetemperatur	3000/4000 Kelvin
Farve	white
CRI	90
UGR ≤	19
Højde	10 cm
Diameter	40 cm
Nettovægt	2.15 kg
Bruttovægt	3.55 kg
Indbygningsdybde	13 cm
Installations diameter	39 cm

Tilbehør

1006871	NUMINOS® PROJEC-TOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / white
1006870	NUMINOS® PROJEC-TOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / black
1008673	Strain relief through-wirable , for DALI dimmable drivers: 1008666, 1008667, 1008668
1008667	LED driver 23W , 100-700mA, DALI
1008672	Strain relief , standard, for DALI-dimmable drivers: 1008666, 1008667, 1008668
1008699	
1008663	LED driver 20W , 350-500mA, PHASE