




MEDO® 60

recessed ceiling light, frame, 3000/4000K, 80°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frame-less. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



Tekniske data

Item no.	1008633
IP klasse	IP20
Montering	Recessed
Sekundær strøm / spænding	1000 mA
IP Tæthedsgad	III
Watt	33 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	4600/4600 lm
Farvetemperatur	3000/4000 Kelvin
Farve	white
CRI	90
UGR ≤	19
Højde	12.5 cm
Diameter	61.5 cm
Nettovægt	4.5 kg
Bruttovægt	8 kg
Indbygningsdybde	16 cm
Installations diameter	61 cm

Tilbehør

1008669	LED driver 53W , 650-1400mA, DALI
1008701	
1006871	NUMINOS® PROJEC- TOR XS , recessed cei- ling light, 2700 K, 40°, cy- lindrical, black / white
1006870	NUMINOS® PROJEC- TOR XS , recessed cei- ling light, 2700 K, 40°, cy- lindrical, black / black
1008674	Strain relief standard , for DALI dimmable drivers: 1008669
1008665	LED driver 40W , 700-1050mA, PHASE
1008702	