




# MEDO® 90

recessed ceiling light, frame, 3000/4000K, 80°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frame-less. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



## Tekniske data

|                           |                  |
|---------------------------|------------------|
| Item no.                  | 1008635          |
| IP klasse                 | IP20             |
| Montering                 | Recessed         |
| Sekundær strøm / spænding | 1000 mA          |
| IP Tæthedsgad             | III              |
| Watt                      | 66 W             |
| Min omgivelsestemperatur  | -20 °C           |
| Max omgivelsestemperatur  | 45 °C            |
| Lumen                     | 9200/9500 lm     |
| Farvetemperatur           | 3000/4000 Kelvin |
| Farve                     | white            |
| CRI                       | 90               |
| UGR ≤                     | 19               |
| Højde                     | 12.5 cm          |
| Diameter                  | 92 cm            |
| Nettovægt                 | 9.1 kg           |
| Bruttovægt                | 15.6 kg          |
| Indbygningsdybde          | 21 cm            |
| Installations diameter    | 91 cm            |

Tilbehør

|         |                                                                                                        |
|---------|--------------------------------------------------------------------------------------------------------|
| 1008669 | LED driver 53W ,<br>650-1400mA, DALI                                                                   |
| 1008701 |                                                                                                        |
| 1006871 | NUMINOS® PROJEC-<br>TOR XS , recessed cei-<br>ling light, 2700 K, 40°, cy-<br>lindrical, black / white |
| 1006870 | NUMINOS® PROJEC-<br>TOR XS , recessed cei-<br>ling light, 2700 K, 40°, cy-<br>lindrical, black / black |
| 1008674 | Strain relief standard , for<br>DALI dimmable drivers:<br>1008669                                      |
| 1008665 | LED driver 40W ,<br>700-1050mA, PHASE                                                                  |
| 1008702 |                                                                                                        |