



## ORDI II

**Pole 45, Free-standing lamp, Square, 2200/3000 K, IP65, Black**

The ORDI II bollard light is an extension to the successful ORDI family and sets new standards in design and technology. With an optimised design, it offers improved technical specifications such as an IP65 protection rating, a sea-air resistant coating, and a robust IK07 classification. These properties make the light ideal for outdoor use, even under extreme conditions such as rain, wind, or salty air. Thanks to the CCT switch, the colour temperature can be flexibly adjusted. The insect-friendly 2,200 K is less attractive to insects due to its lower proportion of blue, while 3,000 K is suitable for functional lighting. The light has an impressive service life of 50,000 hours and is available in the colour black. It comes in two heights - 45 cm and 70 cm - and is ideal for the stylish and safe illumination of pathways. The dimmable versions of the ORDI II bollard light allow the flexible adjustment of the light intensity, for a customised lighting concept.

## TECHNICAL DATA

|                                       |                             |
|---------------------------------------|-----------------------------|
| Item no.                              | 1008725                     |
| IP Code                               | IP65                        |
| Impact resistance class               | IK 07                       |
| Impact resistance                     | 2 Joule                     |
| Assembly                              | Surface                     |
| Assembly details                      | Ground                      |
| Dimmable                              | Yes                         |
| Dimming technology                    | Leading edge, trailing edge |
| Number of through-wires               | 210                         |
| Primary nominal voltage               | 220-240V ~50/60 Hz          |
| Secondary power / voltage             | 240 mA                      |
| Safety class                          | I                           |
| Wattage                               | 9.5 W                       |
| Minimum ambient temperature           | -25 °C                      |
| Maximum ambient temperature           | 45 °C                       |
| Number of luminaires at LS B16A       | 210                         |
| Number of luminaires at LS C16A       | 210                         |
| Level of inrush current               | 4.1 A                       |
| Duration of inrush current            | 81 µs                       |
| Temperature at glass (light emission) | 55 °C                       |
| Lumen                                 | 700/850 lm                  |
| Colour temperature                    | 2200/3000 Kelvin            |

## Light Source

|  |   |
|--|---|
|  |  |
|--|---|

|                       |         |
|-----------------------|---------|
| <b>CRI</b>            | 80      |
| <b>Service life</b>   | 50000 h |
| <b>Risk Group</b>     | 0       |
| <b>Width</b>          | 18 cm   |
| <b>Height</b>         | 45 cm   |
| <b>Depth</b>          | 11.7 cm |
| <b>Net weight</b>     | 2.26 kg |
| <b>Gross weight</b>   | 2.73 kg |
| <b>BIG WHITE Page</b> | 795     |