

TRAIL-LITE® 60

set of 4, recessed floor lights, 3000K, IP67, round, stainless steel / aluminium

The new generation of TRAIL LITE 60 recessed floor and wall lights works with 24V DC and is ideal for decorative orientation lighting on terraces. Its robust design and IP68 rating means the light is protected against dust and temporary immersion, making it ideal for use in outdoor areas. The round recessed light housing made of aluminium is equipped with a long-life, energy-efficient LED. The electrical connection is made via a separately available 24V power adaptor.

TECHNICAL DATA

Item no.	1008841
Number of different light outlets	4
IP Code	IP44/IP67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	24 V
Safety class	11
Wattage	4.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	14
Level of inrush current	100 A
Duration of inrush current	270 µs
Temperature at glass (light emission)	32 °C
Lumen	25 lm
Colour temperature	3000 Kelvin
Color	stainless steel / aluminium
CRI	80



Light Source

A E

Service life	30000 h
Risk Group	1
Height	7.25 cm
Diameter	6 cm
Net weight	2.25 kg
Gross weight	2.5 kg
Installation depth	7.3 cm
Installation diameter	4 cm