


GALEN PRO 60

wall-mounted light, 3000 K, 20 W, DALI 2, touch, 54°, anthracite

The GALEN PRO has a modern, functional design and its asymmetric light distribution makes it ideal for illuminating vertical surfaces - for example, wide area façade lighting or the illumination of advertising spaces and posters. The light is fitted with an IP68 rated 5-pin connector for safe and quick outdoor area installation. Available in two lengths (60 cm and 120 cm), both with DALI control, GALEN PRO offers great flexibility in the design and control of sophisticated outdoor lighting solutions for commercial or residential applications.



TECHNICAL DATA

Item no.	1009107
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI 2, Touch
Number of through-wires	17
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	305 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	17
Number of luminaires at LS C16A	28
Level of inrush current	31 A
Duration of inrush current	262 µs
Temperature at glass (light emission)	58 °C
Lumen	2300 lm
Colour temperature	3000 Kelvin
Beam angle	54 °

Light Source

	
--	---

Accessories

234354	WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 80 cm
--------	---

Color	anthracite
CRI	80
Service life	50000 h
Risk Group	1
Width	60 cm
Height	6.2 cm
Depth	11.1 cm
Net weight	1.69 kg
Gross weight	2.1 kg