


## PARA CONE 14

## 3-phase system light, GU10, aluminium

With their distinctive conical reflector, PARA CONE lights provide a warm, atmospheric light - perfect for modern residential and contract applications. Available in a range of sizes and trendy colours, the range is characterised by its clear design features and high-quality finish. A wide range of mounting options are available for maximum design freedom: The lights are available as pendant lights with an open cable end, with a ceiling rosette or for 1-phase and 3-phase track systems, each with a compatible adapter. The range also includes spots for both track systems. Depending on the version, the PARA CONE lights are equipped with a GU10 or E27 base, allowing the lamp to be easily replaced at any time. A particular highlight is that the lights can be flexibly combined in a variety of ways to create clouds of light, enabling creative and individual lighting installations. Experience lighting design with character -PARA CONE by SLV.



## **TECHNICAL DATA**

| Item no.                  | 1009139                 |
|---------------------------|-------------------------|
| Socket                    | GU10                    |
| Number of sockets         | 1                       |
| Tilt range                | 80 °                    |
| Horizontal rotation range | 300 °                   |
| Rotating or tilting       | rotary bar and tiltable |
| IP Code                   | IP20                    |
| Primary nominal voltage   | 220-240V ~50/60 Hz      |
| Safety class              | I                       |
| Wattage                   | 25 W                    |
| Color                     | aluminum/aluminum       |
| Height                    | 22.5 cm                 |
| Diameter                  | 13.5 cm                 |
| Net weight                | 0.33 kg                 |
| Gross weight              | 0.588 kg                |
|                           | •                       |



## Recommended lamp

| 1006321 | LED lamp , T32, GU10,<br>2600 K, dimmable |
|---------|---|