


SIGHT PANEL

3~ spot, DALI, rectangular, 3000K, 65W, 70°, white

SIGHT PANEL - the high-output spot solution for 3-phase track mounting in shops, galleries or exhibition areas. With a 70° beam angle, CRI>90 and optional DALI control, it provides precise, high-quality light exactly where it is needed. The flexible swivel mechanism allows for precise alignment and the easy installation saves time - for perfect staging of any project.



TECHNICAL DATA

Item no.	1009151
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	330 mA
Safety class	I
Wattage	65 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	21
Number of luminaires at LS C16A	35
Level of inrush current	23 A
Duration of inrush current	174 µs
Lumen	10100 lm
Colour temperature	3000 Kelvin
Beam angle	70 °
Color	white
CRI	90

Light Source

	
--	---

UGR ≤	25
Service life	50000 h
Length	58 cm
Width	19 cm
Height	6.5 cm
Net weight	2.11 kg
Gross weight	2.47 kg