




## BATTEN P 1500 72

### 830/840/850 WH

The BATTEN P light family from the SLVtec range offers powerful and flexible LED lighting solutions that are ideal for the energy-efficient refurbishment of existing T8/T5 fluorescent lamp installations. With a light output of up to 150lm/W and a lifespan of 100,000 hours (L80B10), they provide a durable, economical solution for commercial applications such as offices, schools, retail and infrastructure. The lights are available in three lengths (600, 1200, 1500 mm) and have an integrated multi-lumen and multi-CCT function: four output levels and three light colours (3,000/4,000/5,000 K) can be set on site using a DIP switch. Versions with integrated DALI control, sensors or emergency module (3h) are also available for maximum flexibility in lighting design. With its robust aluminium and polycarbonate (IP20, IK04) housing and simple assembly, the BATTEN P is ideal for demanding projects. An optional accessory 2m steel cable suspension kit completes the system and allows flexible mounting options such as ceiling or pendant mounting.



## TECHNICAL DATA

|                                 |                       |
|---------------------------------|-----------------------|
| Item no.                        | 1009255               |
| IP Code                         | IP20                  |
| Impact resistance class         | IK 04                 |
| Assembly                        | Surface               |
| Assembly details                | Ceiling, Wall         |
| Primary nominal voltage         | 220-240V ~0/50/60 Hz  |
| Secondary power / voltage       | 200-350 mA            |
| Safety class                    | I                     |
| Wattage                         | 28 W                  |
| Ambient temperature             | 80 °C                 |
| Minimum ambient temperature     | -20 °C                |
| Maximum ambient temperature     | 40 °C                 |
| Number of luminaires at LS B16A | 26                    |
| Number of luminaires at LS C16A | 43                    |
| Level of inrush current         | 15 A                  |
| Duration of inrush current      | 272 µs                |
| Lumen                           | 7200/6700/6700 lm     |
| Colour temperature              | 5000/4000/3000 Kelvin |
| Color                           | white                 |
| CRI                             | 80                    |
| Service life                    | 100000 h              |
| Length                          | 150 cm                |

## Light Source

|  |   |
|--|---|
|  |  |
|--|---|

## Accessories

|         |                              |
|---------|------------------------------|
| 1009262 | BATTEN P SCK2000 ,<br>2000mm |
|---------|------------------------------|

|              |         |
|--------------|---------|
| Width        | 5.6 cm  |
| Height       | 6.5 cm  |
| Net weight   | 0.95 kg |
| Gross weight | 22 kg   |