


NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |              |
|-----------------------------------|--------------|
| Item no.                          | 1009276      |
| Number of different light outlets | 1            |
| IP Code                           | IP20         |
| Assembly                          | Recessed     |
| Assembly details                  | Ceiling      |
| Secondary power / voltage         | 200 mA       |
| Safety class                      | III          |
| Wattage                           | 6.9 W        |
| Minimum ambient temperature       | -20 °C       |
| Maximum ambient temperature       | 40 °C        |
| Lumen                             | 900 lm       |
| Colour temperature                | 2700 Kelvin  |
| Beam angle                        | 40 °         |
| Color                             | black/chrome |
| CRI                               | 90           |
| UGR ≤                             | 22           |
| Service life                      | 50000 h      |
| Risk Group                        | 1            |
| Height                            | 4.5 cm       |
| Diameter                          | 6.5 cm       |
| Net weight                        | 0.1 kg       |
| Gross weight                      | 0.2 kg       |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093755 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                    |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser     |
| 1010695 | LED driver , 21W, 200 mA, DALI     |
| 1010703 | LED driver , 23W, 200 mA, DALI     |
| 1005612 | NUMINOS® XS , diffuser             |
| 1010699 | LED driver , 10W, 200 mA, PHASE    |
| 1005615 | NUMINOS® XS , black diffuser       |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1010126 | NUMINOS® XS , reflector, copper    |
| 1010125 | NUMINOS® XS , reflector, gold      |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 11 cm  |
| Installation diameter | 5.5 cm |