


NUMINOS® XS

Recessed ceiling light, 4000 K, 40°, IP20, round, black

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| Item no. | 1009310 |
|-----------------------------------|-------------|
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 6.9 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 1000 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 22 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 4.5 cm |
| Diameter | 6.5 cm |
| Net weight | 0.1 kg |
| Gross weight | 0.2 kg |
| | |



Light Source

| 2093754 | D |
|-------------|------------------------------------|
| Accessories | |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1010126 | NUMINOS® XS , reflector, copper |
| 1010695 | LED driver , 21W, 200 mA, DALI |
| 1010703 | LED driver , 23W, 200 mA, DALI |
| 1005612 | NUMINOS® XS , diffuser |
| 1010699 | LED driver , 10W, 200 mA, PHASE |
| 1005615 | NUMINOS® XS , black diffuser |
| 1010125 | NUMINOS® XS , reflector, gold |
| 1005613 | NUMINOS® XS , transparent diffuser |

| Shape of cut-out | round |
|-----------------------|--------|
| Installation depth | 11 cm |
| Installation diameter | 5.5 cm |