


## NUMINOS® XS

**Recessed ceiling light, 4000 K, 40°, IP20, round, black / white**

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009311     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 200 mA      |
| Safety class                      | III         |
| Wattage                           | 6.9 W       |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 1000 lm     |
| Colour temperature                | 4000 Kelvin |
| Beam angle                        | 40 °        |
| Color                             | black/white |
| CRI                               | 90          |
| UGR ≤                             | 22          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 4.5 cm      |
| Diameter                          | 6.5 cm      |
| Net weight                        | 0.1 kg      |
| Gross weight                      | 0.2 kg      |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093754 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                    |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser     |
| 1010126 | NUMINOS® XS , reflector, copper    |
| 1010695 | LED driver , 21W, 200 mA, DALI     |
| 1010703 | LED driver , 23W, 200 mA, DALI     |
| 1005612 | NUMINOS® XS , diffuser             |
| 1010699 | LED driver , 10W, 200 mA, PHASE    |
| 1005615 | NUMINOS® XS , black diffuser       |
| 1010125 | NUMINOS® XS , reflector, gold      |
| 1005613 | NUMINOS® XS , transparent diffuser |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 11 cm  |
| Installation diameter | 5.5 cm |