


NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® GIMBLE S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009426
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1050 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	white/chrome
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	7 cm
Diameter	10 cm
Net weight	0.188 kg

Light Source

2093742	
---------	---

Accessories

1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honey-comb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1010680	NUMINOS® S , Prismatic diffuser
1010128	NUMINOS® S , reflector, copper
1010127	NUMINOS® S , reflector, gold

Gross weight	0.288 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	9 cm