


## NUMINOS® S

**Recessed ceiling light, 3000 K, 20°, IP20, round, black**

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 6.7 watts, luminous flux of 1050 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009451     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 200 mA      |
| Safety class                      | III         |
| Wattage                           | 6.7 W       |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 1050 lm     |
| Colour temperature                | 3000 Kelvin |
| Beam angle                        | 20 °        |
| Color                             | black       |
| CRI                               | 90          |
| UGR ≤                             | 19          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 5.2 cm      |
| Diameter                          | 8 cm        |
| Net weight                        | 0.13 kg     |
| Gross weight                      | 0.23 kg     |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093839 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010128 | NUMINOS® S , reflector, copper   |
| 1010681 | NUMINOS® S , frosted diffuser    |
| 1010682 | NUMINOS® S , Elliptical diffuser |
| 1010679 | NUMINOS® S , Honey-comb diffuser |
| 1010695 | LED driver , 21W, 200 mA, DALI   |
| 1010703 | LED driver , 23W, 200 mA, DALI   |
| 1010699 | LED driver , 10W, 200 mA, PHASE  |
| 1010127 | NUMINOS® S , reflector, gold     |
| 1010680 | NUMINOS® S , Prismatic diffuser  |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 8 cm   |
| Installation diameter | 6.8 cm |