


The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 6.7 watts, luminous flux of 1050 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009453
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black/chrome
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.23 kg

Light Source

2093839	
---------	---

Accessories

1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honey-comb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1010680	NUMINOS® S , Prismatic diffuser
1010128	NUMINOS® S , reflector, copper
1010127	NUMINOS® S , reflector, gold

Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm