


Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 6.7 watts, a luminous flux of 1050 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |              |
|-----------------------------------|--------------|
| Item no.                          | 1009486      |
| Number of different light outlets | 1            |
| IP Code                           | IP20         |
| Assembly                          | Recessed     |
| Assembly details                  | Ceiling      |
| Secondary power / voltage         | 200 mA       |
| Safety class                      | III          |
| Wattage                           | 6.7 W        |
| Minimum ambient temperature       | -20 °C       |
| Maximum ambient temperature       | 40 °C        |
| Lumen                             | 1050 lm      |
| Colour temperature                | 4000 Kelvin  |
| Beam angle                        | 55 °         |
| Color                             | white/chrome |
| CRI                               | 90           |
| UGR ≤                             | 22           |
| Service life                      | 50000 h      |
| Risk Group                        | 1            |
| Height                            | 5.2 cm       |
| Diameter                          | 8 cm         |
| Net weight                        | 0.13 kg      |
| Gross weight                      | 0.23 kg      |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093742 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010681 | NUMINOS® S , frosted diffuser    |
| 1010682 | NUMINOS® S , Elliptical diffuser |
| 1010679 | NUMINOS® S , Honey-comb diffuser |
| 1010695 | LED driver , 21W, 200 mA, DALI   |
| 1010703 | LED driver , 23W, 200 mA, DALI   |
| 1010699 | LED driver , 10W, 200 mA, PHASE  |
| 1010680 | NUMINOS® S , Prismatic diffuser  |
| 1010128 | NUMINOS® S , reflector, copper   |
| 1010127 | NUMINOS® S , reflector, gold     |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 8 cm   |
| Installation diameter | 6.8 cm |