


NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009574                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 350 mA                  |
| Safety class                      | III                     |
| Wattage                           | 12 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 1800 lm                 |
| Colour temperature                | 3000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white/black             |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 9.5 cm                  |
| Diameter                          | 13.5 cm                 |
| Net weight                        | 0.41 kg                 |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093856 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010704 | LED driver , 23W, 350 mA, DALI   |
| 1010700 | LED driver , 20W, 350 mA, PHASE  |
| 1010683 | NUMINOS® M , Honey-comb diffuser |
| 1010686 | NUMINOS® M , Elliptical diffuser |
| 1010684 | NUMINOS® M , Prismatic diffuser  |
| 1010696 | LED driver , 21W, 350 mA         |
| 1010685 | NUMINOS® M , frosted diffuser    |
| 1010129 | NUMINOS® M , reflector, gold     |
| 1010130 | NUMINOS® M , reflector, copper   |

|                       |         |
|-----------------------|---------|
| Gross weight          | 0.56 kg |
| Shape of cut-out      | round   |
| Installation depth    | 9.5 cm  |
| Installation diameter | 12 cm   |