


## NUMINOS® M

**Recessed ceiling light, 2700 K, 40°, IP20, round, black / white**

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The various downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1700 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009599     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 350 mA      |
| Safety class                      | III         |
| Wattage                           | 12 W        |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 1700 lm     |
| Colour temperature                | 2700 Kelvin |
| Beam angle                        | 40 °        |
| Color                             | black/white |
| CRI                               | 90          |
| UGR ≤                             | 19          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 6.8 cm      |
| Diameter                          | 10.5 cm     |
| Net weight                        | 0.22 kg     |
| Gross weight                      | 0.28 kg     |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093870 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010704 | LED driver , 23W, 350 mA, DALI   |
| 1010700 | LED driver , 20W, 350 mA, PHASE  |
| 1010129 | NUMINOS® M , reflector, gold     |
| 1010683 | NUMINOS® M , Honey-comb diffuser |
| 1010686 | NUMINOS® M , Elliptical diffuser |
| 1010684 | NUMINOS® M , Prismatic diffuser  |
| 1010696 | LED driver , 21W, 350 mA         |
| 1010685 | NUMINOS® M , frosted diffuser    |
| 1010130 | NUMINOS® M , reflector, copper   |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 7.5 cm |
| Installation diameter | 9 cm   |