


NUMINOS® MOVE M

Recessed ceiling light, 3000 K, 40°, IP20, round, white

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1800 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

Item no.	1009680
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	13.5 cm
Net weight	0.35 kg

Light Source

2093856		Gross weight	0.45 kg
Accessories			
1010704	LED driver , 23W, 350 mA, DALI	Shape of cut-out	round
1010700	LED driver , 20W, 350 mA, PHASE	Installation depth	10 cm
1010129	NUMINOS® M , reflector, gold	Installation diameter	12 cm
1010683	NUMINOS® M , Honeycomb diffuser		
1010686	NUMINOS® M , Elliptical diffuser		
1010684	NUMINOS® M , Prismatic diffuser		
1010696	LED driver , 21W, 350 mA		
1010685	NUMINOS® M , frosted diffuser		
1010130	NUMINOS® M , reflector, copper		