


## NUMINOS® GIMBLE L

Recessed ceiling light, 4000 K, 40°, IP20, round, black

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009742                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 500 mA                  |
| Safety class                      | III                     |
| Wattage                           | 17 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 2700 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 11.5 cm                 |
| Diameter                          | 16 cm                   |
| Net weight                        | 0.606 kg                |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093752 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010689 | NUMINOS® L , Frosted diffuser    |
| 1010132 | NUMINOS® L , reflector, copper   |
| 1010697 | LED driver , 21W, 500 mA         |
| 1010687 | NUMINOS® L , Honey-comb diffuser |
| 1010701 | LED driver , 19 W, 500 mA, PHASE |
| 1010688 | NUMINOS® L , Prismatic diffuser  |
| 1010690 | NUMINOS® L , Elliptical diffuser |
| 1010131 | NUMINOS® L , reflector, gold     |
| 1010705 | LED driver , 36W, 500 mA, DALI   |

|                       |          |
|-----------------------|----------|
| Gross weight          | 0.756 kg |
| Shape of cut-out      | round    |
| Installation depth    | 11.5 cm  |
| Installation diameter | 14.5 cm  |