

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17 watts, luminous flux of 2500 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                   |              |
|-----------------------------------|--------------|
| Item no.                          | 1009791      |
| Number of different light outlets | 1            |
| IP Code                           | IP20         |
| Assembly                          | Recessed     |
| Assembly details                  | Ceiling      |
| Secondary power / voltage         | 500 mA       |
| Safety class                      | III          |
| Wattage                           | 17 W         |
| Minimum ambient temperature       | -20 °C       |
| Maximum ambient temperature       | 40 °C        |
| Lumen                             | 2500 lm      |
| Colour temperature                | 3000 Kelvin  |
| Beam angle                        | 55 °         |
| Color                             | white/chrome |
| CRI                               | 90           |
| UGR ≤                             | 22           |
| Service life                      | 50000 h      |
| Risk Group                        | 1            |
| Height                            | 8.5 cm       |
| Diameter                          | 13 cm        |
| Net weight                        | 0.434 kg     |
| Gross weight                      | 0.584 kg     |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093856 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010689 | NUMINOS® L , Frosted diffuser    |
| 1010697 | LED driver , 21W, 500 mA         |
| 1010687 | NUMINOS® L , Honey-comb diffuser |
| 1010701 | LED driver , 19 W, 500 mA, PHASE |
| 1010688 | NUMINOS® L , Prismatic diffuser  |
| 1010690 | NUMINOS® L , Elliptical diffuser |
| 1010705 | LED driver , 36W, 500 mA, DALI   |
| 1010132 | NUMINOS® L , reflector, copper   |
| 1010131 | NUMINOS® L , reflector, gold     |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 8.5 cm |
| Installation diameter | 12 cm  |