


## NUMINOS® L

**Recessed ceiling light, 4000 K, 40°, IP20, round, black**

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2700 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009795     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 500 mA      |
| Safety class                      | III         |
| Wattage                           | 17 W        |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 2700 lm     |
| Colour temperature                | 4000 Kelvin |
| Beam angle                        | 40 °        |
| Color                             | black       |
| CRI                               | 90          |
| UGR ≤                             | 22          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 8.5 cm      |
| Diameter                          | 13 cm       |
| Net weight                        | 0.44 kg     |
| Gross weight                      | 0.59 kg     |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093752 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1010689 | NUMINOS® L , Frosted diffuser    |
| 1010132 | NUMINOS® L , reflector, copper   |
| 1010697 | LED driver , 21W, 500 mA         |
| 1010687 | NUMINOS® L , Honey-comb diffuser |
| 1010701 | LED driver , 19 W, 500 mA, PHASE |
| 1010688 | NUMINOS® L , Prismatic diffuser  |
| 1010690 | NUMINOS® L , Elliptical diffuser |
| 1010131 | NUMINOS® L , reflector, gold     |
| 1010705 | LED driver , 36W, 500 mA, DALI   |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 8.5 cm |
| Installation diameter | 12 cm  |