


## NUMINOS® MOVE L

white/chrom recessed ceiling light 3000 K 55°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® MOVE DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2500 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



### TECHNICAL DATA

Item no.	1009845
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2500 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white/chrome
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	9.3 cm
Diameter	16 cm
Net weight	0.51 kg

## Light Source

2093856		<b>Gross weight</b>	0.66 kg
<b>Accessories</b>		<b>Shape of cut-out</b>	round
1010689	NUMINOS® L , Frosted diffuser	<b>Installation depth</b>	10.5 cm
1010697	LED driver , 21W, 500 mA	<b>Installation diameter</b>	14.5 cm
1010687	NUMINOS® L , Honey-comb diffuser		
1010701	LED driver , 19 W, 500 mA, PHASE		
1010688	NUMINOS® L , Prismatic diffuser		
1010690	NUMINOS® L , Elliptical diffuser		
1010705	LED driver , 36W, 500 mA, DALI		
1010132	NUMINOS® L , reflector, copper		
1010131	NUMINOS® L , reflector, gold		