

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® GIMBLE XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009878                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 24 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 3500 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | white/chrome            |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 13.5 cm                 |
| Diameter                          | 19 cm                   |
| Net weight                        | 0.8 kg                  |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093865 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                   |
|---------|-----------------------------------|
| 1010698 | LED driver , 30W, 700 mA          |
| 1010706 | LED driver , 36W, 700 mA, DALI    |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010692 | NUMINOS® XL , Prismatic diffuser  |
| 1010702 | LED driver , 30W, 700 mA, PHASE   |
| 1010693 | NUMINOS® XL , Frosted diffuser    |
| 1010691 | NUMINOS® XL , Honeycomb diffuser  |
| 1010133 | NUMINOS® XL , reflector, gold     |
| 1010134 | NUMINOS® XL , reflector, copper   |

|                       |         |
|-----------------------|---------|
| Gross weight          | 1.05 kg |
| Shape of cut-out      | round   |
| Installation depth    | 13.5 cm |
| Installation diameter | 17.5 cm |